

MODEL 305	SPECIFICATIONS
ANTENNA TYPE	Heavy duty omni-directional MIMO 2xLTE / 2xWLAN patch antenna for roof mounting on trucks, trailers etc. * LOW PROFILE DESIGN * CAR-WASH PROOF * NO GROUNDPLANE NEEDED
LTE / WLAN Antenna: FREQUENCY IMPEDANCE POLARISATION GAIN (dBi) VSWR	2 x LTE MHz: 698-960 (1) / 1710-2170 (2) / 2300-2690 (3) 2 x WLAN MHz: 2400-2485 (1) / 5250-5850 (2) Nom. 50 Ω Vertical LTE (1) 2 / (2) 5 / (3) 5 WLAN (1) 4 / (2) 6 < 2.2
MAX. POWER	20 Watt
COLOUR	Black
DIMENSIONS/ BUILD-IN DEPTH	Ø 100 x 60 mm / Approx. 16 mm
WEIGHT	Approx. 200 g
MOUNTING	Preferable on horizontal surface (Mounting hole Ø 16 mm)
MATERIAL	Base: PA6 30% Radome: PA6 30% IP67 Classified (when mounted on vehicle); UV-resistance
TEMPERATURE	-40°C - +80°C

MOUNT TYPE	Bolt-on type with double self-adhesive tape for effective sealing
CABLE / CONNECTOR	2 x LTE: ca. 0,30 m RG316 cable and Fakra (m) (RED) 2 x WLAN: ca. 0,30 m RG316 cable and Fakra (m) (BEIGE)

