

colinear Mobile Antenna for the 4m, 2m and TETRA Bands

DESCRIPTION

- External antenna whip mounted on the GPS-Combi mount.
- GPS-antenna for fixed installations.
- Polyethylene-covered flexible whip.
- Easily removable whip for car wash.
- Full hemispherical coverage.
- Built-in high gain, low noise amplifier.
- Right-Hand Circular Polarization antenna (RHCP).
- 5 V supply voltage (3 V respectively 12 V available on request).
- DC supply via RF-connector.
- Matching unit (BBMU) included.

GPS Antenna	
P1dB (GPS Amplifier)	Approx. +7 dBm
Gain (GPS)	28 dBic in axial direction (typ.)
Noise Figure (GPS Amplifier)	< 1 dB (typ.)
Gain (GPS Amplifier)	> 30 dB (typ.)
VSWR (GPS Amplifier)	< 2.0:1
Operating Temperature Range (GPS)	-35 to 75 °C
Installation Torque (GPS)	4 ± 0.5 Nm
Frequency (GPS)	1575 MHz
Weight (GPS)	0.114 kg / 0.25 lb
Power Supply (GPS)	5 ± 0.5 VDC (3 V resp. 12 V on request)
Current Consumption (GPS Amplifier)	0.025 mA
Dimensions (GPS)	Approx. 30 x 89 mm
Colour (GPS)	Black
Materials (GPS)	Cu-nite brass, Stainless steel, Reinforced thermoplastic

ORDERING


Type	Product No.	Description
GPS-C 4/2/TETRA-S BBMU	132000084	MAX.ROOF THICKNESS 2.5 mm
GPS-C 4/2/TETRA-S BBMU/7mm	132000096	ROOF THICKNESS: 3.5 - 7.5 mm




SPECIFICATIONS

Electrical		
Model	GPS-C 4/2/TETRA-S BBMU/...	GPS-COMBI MOUNT
Frequency	4 m: 74.2 - 87.5 MHz 2 m: 167.5 - 174 MHz 70 cm: 380 - 400 MHz	
Antenna Type	Collinear mobile antenna	Active patch antenna
Max. Input Power	25 W	
Polarisation	Vertical	Circular
Pattern Type	Hemispherical	
Impedance	50 Ω	50 Ω
VSWR	74.2 - 77.7 and 84 - 87.5 MHz: = 2.5:1 167.5 - 169.5 and 172 - 174 MHz: = 2.0:1 380 - 400 MHz: = 2.0:1	
Gain (EIA RS-329-1)	4 m: approx.. -3 dB 2 m: approx. -4 dB 70 cm: approx. 2 dB (acc. to EIA RS-329-1)	
Cross Polar Attenuation	> 10 dB (typ.)	
Selectivity	> 45 dB down @ +/- 45 MHz	
Mechanical		
Connection(s)	FME (male for GPS) + FME (female for mobile antenna)	
Materials	Whip: Glass fibre whip with copper wire winding, polyethylene-covered Black-chromed brass Spring: Black-chromed stainless steel	
Colour	Black	
Max. Roof Thickness	2.5 mm / 0.10 in.	
Height	670 mm / 26.38 in.	
Weight	0.06 kg / 0.13 lb	
Mounting	On the GPS-Combi mount	

ADDITIONAL DATA




MOUNTING INSTRUCTIONS





Do not use sealer on rubber gasket or other places.

CABLE MOUNTING



TYPICAL RESPONSE CURVES



VERTICAL RADIATION PATTERN

