




RSB -Clip Stainless Steel Hanger . Quantity of cable gripping tabs for the various cable type may be different.

#### FEATURES / BENEFITS

The RSB-Clip is designed for the installation of feeder cables from sizes 1/4" up to 1-5/8". The clip is a universal clamp device and can be used in many mounting configuration. The RSB-Clip is made of stainless steel. The hanger is resistant against all environmental influences. Due to the mechanical construction, a cable deformation is impossible. Therefore, a deterioration of the electrical properties is avoided.



[External Document Links](#)

[Application Note RSB Clip](#)

[Notes](#)

## Technical features

### GENERAL SPECIFICATIONS

|                        |  |                                                                                                                                      |
|------------------------|--|--------------------------------------------------------------------------------------------------------------------------------------|
| Product Line           |  | Coaxial Cable Accessories                                                                                                            |
| Product Type           |  | Hanger                                                                                                                               |
| Hanger Type            |  | RSB-Clip                                                                                                                             |
| Transmission Line Type |  | LCF114<br>LCFS114<br>RLF114<br>RLFW114<br>RAY114<br>RAYB114<br>RLK114<br>RLKW114<br>RLKU114<br>RLV114<br>RLVU114<br>RCF114<br>UCF114 |
| Cable Type             |  | Coaxial Foam Dielectric<br>Radiating Cable                                                                                           |

### MECHANICAL SPECIFICATIONS

|                                  |         |                 |
|----------------------------------|---------|-----------------|
| Cable Size                       |         | 1-1/4           |
| Number of Cable / Waveguide Runs |         | 1               |
| Material                         |         | Stainless Steel |
| Drill Hole Size                  | mm (in) | 8 (0.315)       |

### ACCESSORIES

|                                 |  |                                                  |
|---------------------------------|--|--------------------------------------------------|
| Spare Part / Useful Accessories |  | Cleat : RSB-310<br>Anchor bar fixation : RSB-315 |
|---------------------------------|--|--------------------------------------------------|

### TEMPERATURE SPECIFICATIONS

|                          |         |                         |
|--------------------------|---------|-------------------------|
| Installation Temperature | °C (°F) | -50 to 85 (-58 to 185 ) |
| Operation Temperature    | °C (°F) | -50 to 85 (-58 to 185 ) |
| Storage Temperature      | °C (°F) | -50 to 85 (-58 to 185 ) |



PACKAGING INFORMATION

|                  |         |               |
|------------------|---------|---------------|
| Package Quantity |         | 75            |
| Weight per piece | kg (lb) | 0.024 (0.053) |
| Weight per kit   | kg (lb) | 2.065 (4.553) |